



### SPECIFICATION

Surface Mounted Paper Towel Dispenser shall hold and dispense 200 standard C-fold or 275 standard multi-fold paper towels and shall be fabricated of alloy 18-8 stainless steel, grade 304, 22 gauge. All exposed surfaces shall be No. 4 satin finish and be protected during shipment with a PVC film easily removable after installation. Towel dispensing slot shall have a fully hemmed-in rolled edge for snag-free dispensing and user safety. Door shall be attached to cabinet at bottom with a full length 5mm diameter stainless steel multi-staked piano hinge and shall be held closed with a tumbler lock keyed alike to other ASI JD MacDonald washroom equipment. Structural assembly of body and door components shall be of welded construction. Unit shall be provided with refill viewer slots on each side and shall have internal towel stack guides. Wall below unit shall be protected against uncontrolled door-drop by self-limiting body and hinge construction. Back of unit shall have keyhole slots for hanging on pre-installed screws (by others).

### INSTALLATION

Unit is surface mounted on wall or partition using five (5) No. 10 self tapping screws (supplied by others). Four (4) mounting holes through back are "keyhole" slots for ease of installation on pre-installed screws. Centre top mounting hole is horizontal slot for ease of adjustment and vandal resistant locking. For mounting height standards refer to current Building Code of Australia for able bodied and/or disabled use.


### OPERATION

Towels are self-feeding until supply is depleted. Unit may be refilled with a partial load in-place and will continue to feed properly. Low level of towel supply is indicated from 35% capacity to empty.

### WARRANTY

One year.

**Surface Mounted Paper Towel Dispenser** shall be Model No. 10-0215 as supplied by ASI JD MacDonald.

 All ASI JD MacDonald disabled compliant products when installed must be in accordance with AS1428 to ensure the specified product is complying with all washroom specification requirements.

