


1

Measure and mark hole positions as shown.


Drill mounting holes with 9mm drill bit.



2


Push wall plugs into holes.

Fix mounting plate in position with screws.



3


Slide soap dish, shower holder and tube holder onto riser assembly.



4

Attach riser assembly in position.


Fasten grub screws to secure riser assembly.



5

Apply teflon tape to water outlet thread.


Fasten adaptor onto water outlet thread.



6

Ensure Rubber Washers are inserted into hose and Check Valve is inserted into Hand Shower.

Carefully connect hose to Hand shower and Adaptor.



recommended
working pressure
**150-500
KPa**



maximum hot
water temperature
**75
degrees**

NOTE:

- If the pressure exceeds or is likely to exceed 550kpa, an approved pressure limiting device must be installed.
 - Flush out all pipe work prior to installation.
 - If the water temperature exceeds 75°C, an approved tempering valve must be fitted.
 - Installation should comply with Australian standard AS3500.1 or relevant local authority requirements.
- Showers may not be suitable for use within:
- Gravity-fed water systems
 - Some instantaneous hot water systems; or

- Pressure supply less than 150kPa;
- NOTE: After installing this product, retighten the flow controller housing to prevent removal by hand.

Failure to comply with the above may void all warranties.

WARRANTY:

Please refer to the full warranty statement enclosed with the product before installing. Or visit www.phoenixtapware.com.au to download a copy.

MAINTENANCE AND CARE:

- Products should be cleaned with mild liquid detergent or soap and water.
- Do not use cream cleaners or citrus based cleaning products, as they are abrasive.
- Use of unsuitable cleaning agents may damage the surface. Any damage caused in this way will not be covered by warranty.

DISCLAIMER:

While we aim to ensure the specifications shown are correct at the time of printing, Phoenix Tapware reserves the right to make modifications without prior notice. Always use the physical product measurements for mark-ups and roughing-in as the line drawing shown may differ from the actual product over time.

This product is suitable for all construction methods; Timber; brick; rammed earth etc - Provided it is installed to the guidelines specified in this instruction.
*All measurements are shown in millimeters.